













	Knüppel	Sechskant	Rund	Flach	Winkel	Vierkant
						
	mm	mm	mm	mm	mm	mm
Warmgewalzt	vkt 40 - 120	EN 10061 (DIN 1015) 9 - 62	EN 10060 (DIN 1013) 5,5 - 150 Betonrippen- stahl 14 - 40	EN 10058 (DIN 1017) Breite Stärke 020-120 3-70 125-150 4-70 155-170 5-70 175-190 5-40 195-200 5-25	EN 10056 (DIN 1028) 20 x 20 x 3 bis 110 x 110 x 12	EN 10059 (DIN 1014) 7 x 7 bis 80 x 80
Geschmiedet	vkt 100 - 600		DIN 7527 Blatt 6 90 - 600	DIN 7527 Blatt 6 Stärke: max. 500 Breite: max. 600		DIN 7527 Blatt 6 80 - 500

FERTIGUNGSSPEKTRUM BLANKSTAHL

	Sechskant	Rund	Flach	Vierkant
				
	mm	mm	mm	mm
Kaltgefertigt	EN 10278 h11 (DIN 176) 4 - 70	EN 10278 h9 (DIN 671) gezogen: 3,0 - 30 geschält und druckpoliert: 16 - 150 EN 10278 h8 (DIN 670) geschliffen 3,0 - 30 Betonrippenstahl 3 - 12	EN 10278 h11 (DIN 174) Breite Stärke 10 - 60 3 - 55 61 - 90 5 - 30 91 - 100 15 - 60	EN 10278 h11 (DIN 178) 4 x 4 bis 70 x 70